



The Wet-seal Scope of Works

For the Supply and Installation of Wet-seal's Pond Waterproofing System in Accordance with the Wet-seal Waterproofing Installation Procedures Manual

Wet-seal provides a free telephone support for Architects, Builders, Developers or Other Trade Professionals that require information in relation to this Pond Waterproofing System or information on any of the Wet-seal Systems. Call 1800 025 081 or email technical@wet-seal.ws

Clients Requirements

The Wet-seal Franchisee/Applicator will discuss with the client the specific areas to be waterproofed.

- Check the plans/drawings.
- Determine if scaffolding is required (Builder to provide).
- Obtain instructions from the Client on: Number of ponds to be sealed.
- Number of lineal meters and meters to be waterproofed.

Client's Responsibility

- To give clear instructions - noting they must comply with the Building Code of Australia (BCA).
- Supply plans and instructions if required.
- The Client/Builder or Supervisor to provide a work site that meets Occupation, Health and Safety (OH&S) regulations.
- The area must be clean dry and suitable for the application of the Wet-seal Waterproof System and not contaminated with paints, varnishes, oils, grease, dust, glue or flaking materials, mortar, render, etc.
- The area to be waterproofed must be installed in accordance with the Architects/Manufacturers specifications.
- Provide scaffolding on the job when required (Builder to provide at own expense).
- Drying time - in cool conditions curing will take longer, ensure that the membrane has cured prior to any further work being undertaken.
- Practice duty of care and protect the Wet-seal Pond Waterproofing System from being damaged by others whilst external construction work is being undertaken.
- Protect the membrane from rain, pressure cleaning, etc until full cure has been achieved.
- Wash with mild dishwashing detergent after the membrane has fully cured then flush prior to going into service.
- Allow adequate drying time prior to being filled and flushed before going into service.
- Adequate tests to be carried out prior to putting fish in pond.

Installation of the Wet-seal Pond Waterproofing System

All work undertaken by the installer must comply with the Building Code of Australia (BCA).

"Your Waterproofing Specialists"

1800 025 081

www.wet-seal.ws



Wet-seal Franchisee/Applicator

- Will carry out all works in accordance with the OH&S regulations (this includes Site Induction) and provide a Householder/Occupier Form when required (e.g. on renovation/building where occupant will be in the vicinity of works being carried out).
- Carry out the work in accordance with the Clients written instructions and the current BCA.
- Inspect the area to be waterproofed, to ensure the work to be carried out will meet the Building Code requirements.
- Clean up and prepare the areas to be waterproofed, the time allowed for this is no greater than 15 minutes per house level (additional charges may be incurred if the Client has not presented the area in accordance with the Clients Responsibility section listed above).
- Protect the membrane on completion of the waterproofing unless otherwise instructed not to, this will need to be discussed with the Client/Builder as to who will be supplying the membrane protection then clearly printed on the quotation before the work is undertaken.

Key Areas to Review

- Clean any contaminates from the area to be waterproofed.
- Prime the area to be waterproofed (e.g. liquid primer).
- Mask off when required, for neatness and to protect adjacent surfaces from excess waterproofing.
- Apply waterproofing as per the Wet-seal Installation Procedures Manual.
- The application of the waterproofing will be carried out in a neat, tidy and competent manner.
- Final inspection to ensure if all areas have been waterproofed as per Wet-seal's Installation Procedures Manual and the current BCA and the Builders instructions.
- Membrane protection is required prior to going into service.
- The applicator will remove any of their consumables prior to leaving the site.

Damage to the Waterproofing System

No liability is accepted for damage - accidental or otherwise - caused to the Wet-seal Waterproofing System after the application of the Wet-seal Pond Waterproofing System is completed.

Any repairs will be quoted separately and must be accepted in writing prior to the commencement of work.

Properly Scheduled Site Visit

Allowance has been made for a single site visit unless otherwise expressly listed in the accompanying quotation. It is the responsibility of the Project Manager and contracting party to ensure that adequate preparations have been made and that the Wet-seal Installation Team can work unencumbered on site. Any delay or unreasonable interruption may be subject to an additional labor/service fee.



Quotation Variance

The quoted Wet-seal Pond Waterproofing System is specific to the building structure plans provided to Wet-seal at the time of quotation. While many minor variances can be accommodated, changes to the overall available lineal meters may require the submission and written approval of an updated quotation.

Terms and Conditions

The Scope of Work must also be referenced against Wet-seal's standard terms and conditions. The terms and conditions are available on Wet-seal's website: www.wet-seal.ws