

The Wet-seal Scope of Works



Wet-seal's Internal Waterproofing System

Wet - seal®

Consultation

Wet-seal (Franchisee/Applicator) will consult with you (Builder/Customer) regarding the wet area waterproofing work required, thus ensuring it complies with the NCC, OR AS3740 based on classification class of building.

Provide Plans/Drawings

All measurements for quotation will be based on the plans/drawings you have provided. Any variations to this information are to be communicated in writing to Wet-seal.

Quotation Variance

The quoted waterproofing system is specific to the construction plans provided to Wet-seal at the time of quotation. While many minor variances can be accommodated, significant changes may require the re-submission and approval of the original quotation.

Site Preparation Prior to Wet-seal Arrival

Area must be prepared by Builder to meet the specifications of NCC OR AS3740 based on classification class of building.

The area to be waterproofed must be clean, dry, and free of contamination.

The substrate, structural flooring, wall sheets and cladding, must be installed in accordance with the Manufacturer's specifications e.g. minimum wood float finish for concrete or sheeting glued/screwed correctly.

Provide a work site that satisfies the relevant Work Health & Safety regulations. Safety of the waterproofer must be considered at all times e.g. Scaffold or safety railing erected to provide a safe work area. Silica dust must be controlled in accordance with Safe Work Australia's requirements.

Falls in floor finishes shall allow all surface water to drain without ponding except for residual water remaining due to surface tension.

Drainage must be adequate to ensure accidental blockage cannot occur. For concrete floor substrates complete with a drainage waste/outlet, scoop out around waste pipe to allow drainage flange to sit flush with substrate surface.

Extra noggins to be installed to allow for increased height of waterproofing if laminated sheeting is being installed.

Plumbing fittings must be correctly fitted. Wet-seal must be able to seal onto base fittings (not spindle) and into drainage flanges and turn up waste risers in accordance with NCC OR AS3740 based on classification class of building.

Flood testing

Allow the membrane to cure for a minimum of 7 days at 25° C and 50% RH before flood testing.

Tiling

Membrane shall be clean, free of dust and contamination prior to tiling for up to 7 days. If tiling after 7 days contact Wet-seal for more information.

When tiling directly over Wet-seal™ Enviro-coat Membranes, polymer modified, flexible cement-based tile adhesives are recommended.

Wet-seal Enviro-coat Membranes have been independently tested and are compatible with quality C2S1 and C2S2 tile adhesives. Ensure that the tile glue is water based.

"Your Waterproofing Specialists"

1800 025 081

www.wet-seal.com.au

The Wet-seal Scope of Works



Wet - seal[®]

Solvent based adhesives are not compatible with Wet-seal™ Enviro-coat Membranes. Premixed (Dispersion) tile adhesives are not recommended. All tiling is to be carried out to AS 3958.1- 2007 “A Guide to The Installation of Ceramic Tiles”.

Properly Scheduled Site Visit

Provide a minimum of seven (7) working days as lead time.

Allowance has been made for a single site visit unless otherwise explicitly listed in the accompanying quotation. It is the responsibility of the Project Manager/Builder and contracting party to ensure that adequate preparation has been made and that the Wet-seal installation team can work unencumbered on site. Any delay or unreasonable interruption may be subject to an additional call back fee prior to the commencement of work.

Duty Of Care - Cure Time & Membrane Protection

- ✓ It is the client's responsibility to ensure the membrane is protected from weather, traffic, or contamination.
- ✓ Allow 48 hours at 25°C/50%RH before any access is permitted to the waterproofed areas.
- ✓ When dry (48 hours at 25°C/50%RH), if not immediately tiled provide protective sheeting to prevent any damage from other trades and UV exposure.
- ✓ Any damage that occurs because of the above will result in the warranty being void.
- ✓ It is the customers duty to protect the membrane, using a fit for purpose protection board to prevent damage, e.g. Corflute, Roof Mate SMTG or RTMX.

Warranty

Wet-seal will provide an Installation Certificate in a timely manner to the Client upon payment. The Installation Certificate will state the warranty time and lists the work carried out by the Wet-seal Independent Franchisee in accordance with the NCC or AS 3740.

In the unlikely event of a defect, send an email to technical@wet-seal.com with your contact details and specifics of the job address and issue. Or call Wet-seal's Technical Department on 1800 025 081. Wet-seal will respond promptly.

In relation to the Wet-seal warranty, no invasive investigation or rectification work can be carried out without written consent from Wet-seal and notification to the Franchisee as this will void warranty.

Liability

If the membrane is damaged at any time, by someone other than the Independent Wet-seal Franchise, the Warranty shall be voided.

No liability whatsoever is accepted for damage – accidental or otherwise – done to the waterproofing membrane after the application of the membrane is completed.

Any damage repairs will be quoted separately and must be accepted in writing prior to the commencement of work.

Terms and Conditions

The Scope of Work must also be referenced against Wet-seal's standard terms and conditions. The terms and conditions are available on Wet-seal's website: www.wet-seal.com.au

"Your Waterproofing Specialists"

1800 025 081

www.wet-seal.com.au